

# Package: rsmatch (via r-universe)

September 17, 2024

**Title** Matching Methods for Time-Varying Observational Studies

**Version** 0.2.1

**Description** Implements popular methods for matching in time-varying observational studies. Matching is difficult in this scenario because participants can be treated at different times which may have an influence on the outcomes. The core methods include: ``Balanced Risk Set Matching" from Li, Propert, and Rosenbaum (2011) <[doi:10.1198/016214501753208573](https://doi.org/10.1198/016214501753208573)> and ``Propensity Score Matching with Time-Dependent Covariates" from Lu (2005) <[doi:10.1111/j.1541-0420.2005.00356.x](https://doi.org/10.1111/j.1541-0420.2005.00356.x)>. Some functions use the 'Gurobi' optimization back-end to improve the optimization problem speed; the 'gurobi' R package and associated software can be downloaded from <<https://www.gurobi.com>> after obtaining a license.

**License** MIT + file LICENSE

**URL** <https://skent259.github.io/rsmatch/>,  
<https://github.com/skent259/rsmatch>

**BugReports** <https://github.com/skent259/rsmatch/issues>

**Depends** R (>= 2.10)

**Imports** dplyr, MASS, Matrix, stats

**Suggests** gurobi, knitr, nbpMatching, Rglpk, rlang, rmarkdown, survival, testthat

**VignetteBuilder** knitr

**Encoding** UTF-8

**LazyData** true

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.2.3

**Repository** <https://skent259.r-universe.dev>

**RemoteUrl** <https://github.com/skent259/rsmatch>

**RemoteRef** HEAD

**RemoteSha** 6aa5b3b7c7109cbcbefa2f46f7f25d7ef0101b4e

## Contents

brsmatch . . . . .	2
coxpsmatch . . . . .	4
oasis . . . . .	6
<b>Index</b>	<b>7</b>

---

brsmatch	<i>Balanced Risk Set Matching</i>
----------	-----------------------------------

---

## Description

Perform balanced risk set matching as described in Li et al. (2001) "Balanced Risk Set Matching". Given a longitudinal data frame with covariate information, along with treatment time, build a MIP problem that matches treated individuals to those that haven't been treated yet (or are never treated) based on minimizing the Mahalanobis distance between covariates. If balancing is desired, the model will try to minimize the imbalance in terms of specified balancing covariates in the final pair output. Each treated individual is matched to one other individual.

## Usage

```
brsmatch(
  n_pairs,
  data,
  id = "id",
  time = "time",
  trt_time = "trt_time",
  covariates = NULL,
  balance = TRUE,
  balance_covariates = NULL,
  exact_match = NULL,
  options = list(time_lag = FALSE, verbose = FALSE, optimizer = c("glpk", "gurobi"))
)
```

## Arguments

n_pairs	The number of pairs desired from matching.
data	A data.frame or similar containing columns matching the id, time, trt_time arguments, and covariates. This data frame is expected to be in tidy, long format, so that id, trt_time, and other variables may be repeated for different values of time. The data.frame should be unique at id and time.
id	A character specifying the id column name (default 'id').
time	A character specifying the time column name (default 'time').
trt_time	A character specifying the treatment time column name (default 'trt_time').

covariates	A character vector specifying the covariates to use for matching (default NULL). If NULL, this will default to all columns except those named by the <code>id</code> , <code>time</code> , and <code>trt_time</code> arguments.
balance	A logical value indicating whether to include balancing constraints in the matching process.
balance_covariates	A character vector specifying the covariates to use for balancing (default NULL). If NULL, this will default to all columns except those named by the <code>id</code> , <code>time</code> , and <code>trt_time</code> arguments.
exact_match	A vector of optional covariates to perform exact matching on. If NULL, no exact matching is done.
options	A list of additional parameters with the following components: <ul style="list-style-type: none"><li>• <code>time_lag</code> A logical value indicating whether the matches should be made on the time period preceding treatment. This can help avoid confounding if treatment happens between two periods.</li><li>• <code>verbose</code> A logical value indicating whether to print information to the console during a potentially long matching process.</li><li>• <code>optimizer</code> The optimizer to use (default 'glpk'). The option 'gurobi' requires an external license and package, but offers speed improvements.</li></ul>

## Details

Note that when using exact matching, the `n_pairs` are split roughly in proportion to the number of treated subjects in each exact matching group. If you would like to control `n_pairs` exactly, we suggest manually performing exact matching, for example with `split()`, and selecting `n_pairs` for each group interactively.

## Value

A data frame containing the pair information. The data frame has columns `id`, `pair_id`, and `type`. `id` matches the input parameter and will contain all ids from the input data frame. `pair_id` refers to the id of the computed pairs; NA values indicate unmatched individuals. `type` indicates whether the individual in the pair is considered as treatment ("trt") or control ("all") in that pair.

## Author(s)

Sean Kent

## References

Li, Yunfei Paul, Kathleen J Propert, and Paul R Rosenbaum. 2001. "Balanced Risk Set Matching." *Journal of the American Statistical Association* 96 (455): 870-82. doi:10.1198/016214501753208573

## Examples

```
if (requireNamespace("Rglpk", quietly = TRUE)) {  
  library(dplyr, quietly = TRUE)  
  pairs <- brsmatch(  
    covariates = "age",  
    balance = TRUE,  
    exact_match = "sex",  
    options = list(verbose = TRUE)  
  )  
}
```

```

    n_pairs = 13,
    data = oasis,
    id = "subject_id",
    time = "visit",
    trt_time = "time_of_ad",
    balance = FALSE
  )

na.omit(pairs)

# evaluate the first match
first_match <- pairs$subject_id[which(pairs$pair_id == 1)]
oasis %>% dplyr::filter(subject_id %in% first_match)
}

```

---

coxpsmatch

*Propensity Score Matching with Time-Dependent Covariates*


---

### Description

Perform propensity score matching as described in Lu (2005) "Propensity Score Matching with Time-Dependent Covariates". Given a longitudinal data frame with covariate information, along with treatment time, match treated individuals to those that haven't been treated yet (or are never treated) based on time-dependent propensity scores from a Cox proportional hazards model. Each treated individual is matched to one other individual, unless the number of pairs is specified.

### Usage

```

coxpsmatch(
  n_pairs = 10^10,
  data,
  id = "id",
  time = "time",
  trt_time = "trt_time",
  covariates = NULL,
  exact_match = NULL,
  options = list(time_lag = FALSE)
)

```

### Arguments

<code>n_pairs</code>	The number of pairs desired from matching.
<code>data</code>	A data.frame or similar containing columns matching the <code>id</code> , <code>time</code> , <code>trt_time</code> arguments, and <code>covariates</code> . This data frame is expected to be in tidy, long format, so that <code>id</code> , <code>trt_time</code> , and other variables may be repeated for different values of <code>time</code> . The data.frame should be unique at <code>id</code> and <code>time</code> .
<code>id</code>	A character specifying the <code>id</code> column name (default 'id').

time	A character specifying the time column name (default 'time').
trt_time	A character specifying the treatment time column name (default 'trt_time').
covariates	A character vector specifying the covariates to use for matching (default NULL). If NULL, this will default to all columns except those named by the id, time, and trt_time arguments.
exact_match	A vector of optional covariates to perform exact matching on. If NULL, no exact matching is done.
options	A list of additional parameters with the following components: <ul style="list-style-type: none"> <li>time_lag A logical value indicating whether the matches should be made on the time period preceding treatment. This can help avoid confounding if treatment happens between two periods.</li> </ul>

### Value

A data frame containing the pair information. The data frame has columns `id`, `pair_id`, and `type`. `id` matches the input parameter and will contain all ids from the input data frame. `pair_id` refers to the id of the computed pairs; NA values indicate unmatched individuals. `type` indicates whether the individual in the pair is considered as treatment ("trt") or control ("all") in that pair.

### Author(s)

Mitchell Paukner

### References

Lu, Bo. 2005. "Propensity Score Matching with Time-Dependent Covariates." *Biometrics* 61 (3): 721-28. doi:10.1111/j.15410420.2005.00356.x

### Examples

```
if (requireNamespace("survival", quietly = TRUE) &
    requireNamespace("nbpMatching", quietly = TRUE)) {
  library(dplyr, quietly = TRUE)
  pairs <- coxpsmatch(
    n_pairs = 13,
    data = oasis,
    id = "subject_id",
    time = "visit",
    trt_time = "time_of_ad"
  )

  na.omit(pairs)

  # evaluate the first match
  first_match <- pairs$subject_id[which(pairs$pair_id == 1)]
  oasis %>% dplyr::filter(subject_id %in% first_match)
}
```

---

oasis

*Longitudinal MRI data in nondemented and demented older adults.*

---

### Description

A dataset containing baseline and time-varying information relating to Alzheimer's disease (AD) based on the [Open Access Series of Imaging Studies](#) (OASIS). This set consists of a longitudinal collection of 51 subjects aged 62 to 92. Each subject was scanned on two or more visits, separated by at least one year for a total of 115 imaging sessions. For each subject, 3 or 4 individual T1-weighted MRI scans obtained in single scan sessions are included.

### Usage

oasis

### Format

A data frame with 115 rows and 11 variables:

**subject\_id** unique subject identifier  
**visit** visit order  
**time\_of\_ad** visit in which a patient first had AD diagnosis  
**m\_f** male or female  
**educ** years of education  
**ses** socioeconomic status (-1 for missing)  
**age** age of patient at visit  
**mr\_delay** MR delay time (contrast)  
**e\_tiv** estimated total intracranial volume  
**n\_wbv** normalized whole brain volume  
**asf** atlas scaling factor

### Details

The data was originally hosted in this Kaggle repository: [https://www.kaggle.com/jboysen/mri-and-alzheimers?select=oasis\\_longitudinal.csv](https://www.kaggle.com/jboysen/mri-and-alzheimers?select=oasis_longitudinal.csv). It has been harmonized for an example analysis for risk set matching based on a reduced sample including patients who go from mild cognitive impairment (MCI) to AD and those patients with MCI throughout.

### Source

[https://www.kaggle.com/jboysen/mri-and-alzheimers?select=oasis\\_longitudinal.csv](https://www.kaggle.com/jboysen/mri-and-alzheimers?select=oasis_longitudinal.csv)

# Index

\* **datasets**

oasis, 6

brsmatch, 2

coxpsmatch, 4

oasis, 6